


Datasheet for: 116073


5/3-way valve, Pneumatic, »4A«, Centre vented, M5

 5/3-way valve, Pneumatic, »4A«, Centre vented, M5,
 Operating pressure 1.5 - 8 bar, Temperature range max. 70
 °C . 5/3-way pilot valves - Pneumatic -

Type number	516.7000
Article number	116073
EAN/barcode	 4047322309776
Your price	45,96 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	M5
Control air port	G 1/8
Exhaust connection	M5
Flow rate	250 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Mid-position exhausted
Page No.	HK465
Page No. AS	AS085
Size	100
Symbol	30
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116073	M5	M5	250 l/min	100	45,96 € / Stk
116079	G 1/2	G 1/2	1600 l/min	400	115,11 € / Stk
116076	G 1/4	G 1/8	550 l/min	200	48,19 € / Stk
116075	G 1/8	G 1/8	550 l/min	200	48,19 € / Stk
116077	G 1/4	G 1/4	950 l/min	300	52,14 € / Stk
116078	G 3/8	G 1/4	950 l/min	300	52,14 € / Stk
116074	G 1/8	G 1/8	400 l/min	100	45,96 € / Stk

More Pictures

