


Datasheet for: 116080


5/3-way valve, Pneumatic, »4A«, Centre aerated, M5

 5/3-way valve, Pneumatic, »4A«, Centre aerated, M5,
 Operating pressure 1.5 - 8 bar, Temperature range max. 70
 °C . 5/3-way pilot valves - Pneumatic -

Type number	516.8000
Article number	116080
EAN/barcode	 4047322309899
Your price	45,96 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	M5
Control air port	G 1/8
Exhaust connection	M5
Flow rate	250 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Mid-position pressurised
Page No.	HK465
Page No. AS	AS085
Size	100
Symbol	31
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116080	M5	M5	250 l/min	100	45,96 € / Stk
116084	G 1/4	G 1/4	950 l/min	300	52,14 € / Stk
116086	G 1/2	G 1/2	1600 l/min	400	115,11 € / Stk
116085	G 3/8	G 1/4	950 l/min	300	52,14 € / Stk
116081	G 1/8	G 1/8	400 l/min	100	45,96 € / Stk
116082	G 1/8	G 1/8	550 l/min	200	48,19 € / Stk
116083	G 1/4	G 1/8	550 l/min	200	48,19 € / Stk

More Pictures

