

Datasheet for: 100781



Filter regulator »Standard-mini« with PC container, 5 µm, G 1/8

Filter regulator »Standard-mini« with PC container incl. pressure gauge and control cabinet nut, 5 µm, Size 0, G 1/8, 0.5 - 10 bar. Compact, reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator. The pressure setting can be locked by pushing the knob down.

Type number	578.00 K-HA
Article number	100781
EAN/barcode	 4047322355216
Your price	46,14 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	40.0 mm
B	167.0 mm
Bowl	Polycarbonate container
C	65.0 mm
Condensate drain	semi-automatic
D	102.0 mm
DN	5.0
Filter rating	5.0 µm
Flow rate	350 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK115
Pressure gauge display max.	16.0 bar

Pressure gauge	0.0 bar
display min.	
Sealant	NBR
Series	Standard-mini
Spring bonnet	POM-brass
Thread	G 1/8

Variants

Article number	Thread	Price
100781	G 1/8	46,14 € / Stk
100782	G 1/4	46,14 € / Stk

More Pictures

