


## Datasheet for: 100518



### Filter »multifix«, PC container, Protective cage, Size 1, G 3/8

Filter »multifix«, PC container and protective cage, 5  $\mu\text{m}$ , Size 1, G 3/8, Input pressure max. 16 bar, Med./ambient temp. max. 60°C . Centrifugal separators with a sintered filter element.

Type number	F 12 S
Article number	100518
EAN/barcode	 4047322130752
Your price	40,19 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

A	47.8 mm
B	152.1 mm
Bowl	Polycarbonate container with protective cage
C	27.0 mm
Condensate drain	Semi-automatic
D	125.1 mm
DN	10.0
Filter rating	5.0 $\mu\text{m}$
Flow rate	2100 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK084
Series	multifix
Size	1
Thread	G 3/8

## Variants

Article number	Thread	Housing	Filter rating	Flow rate	DN	Size	Price
100518	G 3/8	Die-cast zinc	5.0 $\mu\text{m}$	2100 l/min	10.0	1	40,19 € / Stk
100517	G 1/4	Die-cast zinc	5.0 $\mu\text{m}$	2100 l/min	6.0	1	40,19 € / Stk
100519	G 1/2	Die-cast zinc	5.0 $\mu\text{m}$	4000 l/min	15.0	3	64,99 € / Stk
100520	G 3/4	Die-cast zinc	5.0 $\mu\text{m}$	4000 l/min	20.0	3	64,99 € / Stk
100521	G 1	Aluminium	40.0 $\mu\text{m}$	8000 l/min	25.0	5	171,36 € / Stk
133111	G 3/4	Die-cast aluminium	5.0 $\mu\text{m}$	7800 l/min	20.0	4	133,23 € / Stk
133112	G 1	Die-cast aluminium	5.0 $\mu\text{m}$	7800 l/min	25.0	4	133,23 € / Stk

## More Pictures

