


Datasheet for: 116520


2/2-way solenoid valve »2S« NC, directly operated, 230 V, 50 Hz

2/2-way solenoid valve »2S«, Stainless steel, NC, directly operated, 230 V, 50 Hz, Medium temp. max. 80°C/90°C, G 1/8, PN 0-10 bar . Standard series available in two different versions: -Directly operated -Pilot-operated Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MV 1501 ES
Article number	116520
EAN/barcode	 4047322323796
Your price	50,40 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	40.0 mm
C	70.7 mm
DN	3
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. operating pressure	10 bar
Page No.	HK329
Page No. AS	AS049
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/8
Type	1
Valve seat	Stainless steel 1.4301

Variants

Article number	Thread	DN	Price
116520	G 1/8	3	50,40 € / Stk
116526	G 1/2	5	72,37 € / Stk
116524	G 3/8	5	72,37 € / Stk
116522	G 1/4	3	50,40 € / Stk

More Pictures

