

Datasheet for: 116528



2/2-way solenoid valve »2S« NC, directly operated, 24 V DC, G 1/8

2/2-way solenoid valve »2S«, Stainless steel, NC, directly operated, 24 V DC, Medium temp. max. 80 °C/90 °C, G 1/8, PN - 10 bar . Standard series available in two different versions: -Directly operated -Pilot-operated Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MV 1511 ES
-------------	------------

Article number	116528
----------------	--------

EAN/barcode	
-------------	--



4047322323871

Your price	50,40 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	40.0 mm
C	70.7 mm
DN	3
Housing	Stainless steel 1.4301
Internal parts	Stainless steel
Max. operating pressure	10 bar
Page No.	HK329
Page No. AS	AS049
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/8
Type	1
Valve seat	Stainless steel 1.4301

Variants

<i>Article number</i>	<i>Thread</i>	<i>DN</i>	<i>Price</i>
116528	G 1/8	3	50,40 € / Stk
116534	G 1/2	5	72,37 € / Stk
116530	G 1/4	3	50,40 € / Stk
116532	G 3/8	5	72,37 € / Stk

More Pictures

