

No. 1907/2006 (REACH) Printed

revision 17.12.2018 (GB) Version 8.4 RIEGLER LOCK AN 302-60 / 50 ml / 250 ml

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

RIEGLER LOCK AN 302-60 / 50 ml / 250 ml Name of product

Code-Nr. ID-Nr. 114556/-57

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

1-Component Adhesives and Sealants, anaerobic curing

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor RIEGLER & Co. KG

Schützenstr. 27, D-72574 Bad Urach

Phone: +49 (0) 7125/9497-0, Fax: +49 (0) 7125/9497-97

E-Mail: zedok@riegler.de Internet: www.riegler.de

Advice Abteilung eDocumentation Phone : +49 (0) 7125/9497-0

Fax: +49(0)7125/9497-97 E-mail (competent person):

zedok@riegler.de

1.4. Emergency telephone number

Giftnotrufzentrale Bonn **Emergency advice**

Phone : +49(0)228-19 240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
Skin Irrit. 2	H315	
From Locald C	11040	

Eye Irrit. 2 H319 Skin Sens. 1 H317 STOT SE 3 H335

Hazard Statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





No. 1907/2006 (REACH) Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

Signal word

Warning

Hazard Statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

Precautionary Statements

P102	ements Keep out of reach of children.
P261 P264 P271 P272	Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace.
P302 + P352 P304 + P340 P305 + P351 + P338 P312 P332 + P313 P333 + P313 P337 + P313 P362 P363	IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing. Wash contaminated clothing before reuse.
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

Hazardous ingredients for labeling

2-hydroxyethyl methacrylate

2.3. Other hazards

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Description

Anaerobic adhesive / sealant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
79-10-7	201-177-9	acrylic acid	1 - 3	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / Skin Corr. 1A, H314 / Aquatic Acute 1, H400
868-77-9	212-782-2	2-hydroxyethyl methacrylate	1 - 5	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1. H317



No. 1907/2006 (REACH) Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

CAS No	EC No	Name	[% Classification according to Regulation (EC) weight] No 1272/2008 [CLP/GHS]	
80-15-9	201-254-7	cumene hydroperoxide	Operoxide 0,1 < 1 Org. Perox. E, H242 / Acute Tox. 3, H331 Acute Tox. 4, H312 / Acute Tox. 4, H302 / STOT RE 2, H373 / Skin Corr. 1B, H314 / Aquatic Chronic 2, H411	
40220-08-4	254-843-6	(2,4,6-trioxo-1,3,5-triazine-1,3,5(2H,4H,6H)-triyl)tri-2,1-ethanediyl triacrylate	10 - 30	Skin Irrit. 2, H315 / Eye Irrit. 2, H319
REACH				
CAS No	Name			REACH registration number
79-10-7	acrylic acid	erylic acid 01-2119452449-31		
868-77-9	2-hydroxyethyl methacrylate 01-2119490169-29		01-2119490169-29	
80-15-9	cumene hydr	operoxide		01-2119475796-19

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

If swallowed give water to drink.

4.2. Most important symptoms and effects, both acute and delayed Physician's information / possible symptoms

Allergic symptoms

Confusion

skin irritation

Physician's information / possible dangers

Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

sand

Water spray jet



No. 1907/2006 (REACH)
Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3. Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Do not inhale vapours.

Avoid contact with eyes and skin

Hygiene measures

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.



No. 1907/2006 (REACH) Printed

revision 17.12.2018 (GB) Version 8.4 RIEGLER LOCK AN 302-60 / 50 ml / 250 ml

7.2. Conditions for safe storage, including any incompatibilities Requirements for storage rooms and vessels

Keep only in original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Do not store together with reducing agents.

Do not store together with metals.

Further information on storage conditions

Store at +5 till +25 °C.

Protect from heat and direct solar radiation.

Store container at cool and aired place.

7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

! SECTION 8: Exposure controls/personal protection

8.1. Control parameters **DNEL-/PNEC-values**

DNEL worker

CAS No	Substance name	Value	Code Remark		
80-15-9	cumene hydroperoxide	6 mg/m3	DNEL long-term inhalative (systemic)		
868-77-9	2-hydroxyethyl methacrylate	4,9 mg/m3	DNEL long-term inhalative (systemic)		
		1,3 mg/kg bw/day	DNEL long-term dermal (systemic)		
PNEC					
CAS No	Substance name	Value	Code	Remark	
868-77-9	2-hydroxyethyl methacrylate	3,79 mg/kg	PNEC soil, freshwater		
		10 mg/l	PNEC sewage treatment plant (STF	P)	
		0,482 mg/l	PNEC soil, marine water		

! Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;



No. 1907/2006 (REACH) Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Sufficient ventilation and exhaustion.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Colour Odour

liquid green hardly noticeable

Odour threshold not determined

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not determined				
melting point	not determined				
Flash point	> 100 °C				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	ca. 1,1 g/ml				
Vapour density	not determined				
Solubility in water		20 °C			No or low immiscibility
Solubility/other			acetone		teilweise mischbar
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				



No. 1907/2006 (REACH) Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

Value Temperature at Method Remark
ca. 750 mPa*s

Oxidising properties

Viscosity

No information available.

Explosive properties

No information available.

9.2. Other information

No information available.

! SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with strong oxidising agents.

Reactions with reducing agents.

Reactions with Metals.

10.4. Conditions to avoid

Metal, Metal-Salts Keep away from heat.

10.5. Incompatible materials

Substances to avoid

Oxidising agent, strong

Reducing agent, strong

Metal, Metal-Salts

10.6. Hazardous decomposition products

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity/Irritation/Sensitization

Value/Validation Species Method Remark

Skin irritation irritant

Eye irritation irritant - risk of strong eye

injuries

Skin sensitization sensitizing



No. 1907/2006 (REACH)
Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

Experiences made from practice

Sensitization through skin contact possible.

Irritates eyes and skin.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from products of similar composition.

SECTION 12: Ecological information

12.1. Toxicity

No information available.

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

General regulation

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste code No.

Name of waste

08 04 09*

waste adhesives and sealants containing organic solvents or other hazardous

substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR	
14.1. UN number	-	-	-	



No. 1907/2006 (REACH)
Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

	ADR/RID	IMDG	IATA-DGR
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

 $\begin{array}{lll} \textbf{VOC content} & \text{ca.5 \%} \\ \textbf{VOC value} & 40.5 \text{ g/L} \end{array}$

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.3

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state
	route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H400	Very toxic to aquatic life.



No. 1907/2006 (REACH) Printed 21.12.2018

revision 17.12.2018 (GB) Version 8.4 **RIEGLER LOCK AN 302-60 / 50 ml / 250 ml**

H411 Toxic to aquatic life with long lasting effects.