


Datasheet for: 103162



Ball valve standard design, black steel lever, IT/IT, G 1 1/4

Ball valve standard design, black steel lever, IT/IT, nickel-plated brass, Operating temp. -15°C to 90°C, G 1 1/4, PN max. 40 bar . Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Type number	330.07-S
Article number	103162
EAN/barcode	 4047322277631
Your price	40,42 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	130.0 mm
B	63.1 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	32.0
E	13.5 mm
F	13.5 mm
Hand lever	Steel, with plastic coating
L	80.0 mm
Material	Nickel-plated brass
Max. operating temperature	90 °C
Min. operating temperature	-15 °C
PN	40 bar
Page No.	HK270
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
Thread	G 1 1/4
Thread material	Brass with a bare metal surface

Variants

Article number	Thread	DN	Price
103162	G 1 1/4	32.0	40,42 € / Stk
103160	G 3/4	20.0	17,94 € / Stk
103164	G 2	50.0	90,51 € / Stk
103157	G 1/4	8.0	11,76 € / Stk
103163	G 1 1/2	40.0	59,41 € / Stk
103161	G 1	25.0	25,17 € / Stk
103158	G 3/8	10.0	12,35 € / Stk
103159	G 1/2	15.0	13,16 € / Stk
103166	G 3	80.0	247,32 € / Stk
103165	G 2 1/2	65.0	174,90 € / Stk

More Pictures

