


Datasheet for: 115967


5/2-way valve, Manual lever actuation, »4H«, engaging, G 3/8

5/2-way valve, Manual lever actuation, »4H«, engaging, G 3/8, Operating pressure - 8 bar, Temperature range -20 °C to 70 °C . 5/2- and 5/3-way valves - Manually operated -

| | |
|----------------|--|
| Type number | 514.1003 |
| Article number | 115967 |
| EAN/barcode |  4047322311922 |
| Your price | 50,76 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|--|
| Connection | G 3/8 |
| Exhaust connection | G 1/4 |
| Flow rate | 1500 l/min |
| Flow rate measurement | At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar |
| Function | 5/2 |
| Max. operating pressure | 8 bar |
| Max. temperature range | 70 °C |
| Min. temperature range | -20 °C |
| Operation | Bistable |
| Page No. | HK460 |
| Page No. AS | AS082 |
| Size | 300 |
| Symbol | 13 |
| Valve body | Aluminium alloy |

Variants

| Article number | Connection | Exhaust connection | Flow rate | Size | Price |
|----------------|------------|--------------------|------------|------|---------------|
| 115967 | G 3/8 | G 1/4 | 1500 l/min | 300 | 50,76 € / Stk |
| 115965 | G 1/4 | G 1/8 | 850 l/min | 200 | 35,97 € / Stk |
| 115966 | G 1/4 | G 1/4 | 1300 l/min | 300 | 50,76 € / Stk |
| 115964 | G 1/8 | G 1/8 | 750 l/min | 200 | 35,97 € / Stk |

More Pictures

