


Datasheet for: 103030


Pressure switch, Special die casting, G 1/4, 0.2 - 2 bar

Pressure switch, Electr. connection equipment plug A shape, Special die casting, Temperature -20 °C to 80 °C, G 1/4, 0.2 - 2 bar . For converting pneumatic to electrical signals. Designed for use in rough vacuum applications (technical vacuum). Universal switch type, suitable as NC, NO or changeover contact. These devices are free from paint-wetting impairment substances (PWIS).

Type number	DS 5811
Article number	103030
EAN/barcode	 4047322126434
Your price	50,80 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	48.0 mm
Adjusting knob	Aluminium, powder-coated
Adjustment range max.	2.0 bar
Adjustment range min.	0.2 bar
Applications	Pneumatic applications
B	28.0 mm
Connection	G 1/4
Diaphragms	NBR
Housing	Special die-cast material
Max. temperature range	80 °C
Min. temperature range	-20 °C
Page No.	HK338
Protection IP	IP65 (DIN 43650), IP67 (M12x1)
Sealant	NBR
Switching frequency	200/min.
Switching voltage	250 V AC / 28 V DC

Variants

Article number	Adjustment range min.	Adjustment range max.	Price
103030	0.2 bar	2.0 bar	50,80 € / Stk
103031	0.5 bar	8.0 bar	50,80 € / Stk
103032	1.0 bar	16.0 bar	50,80 € / Stk

More Pictures

