


## Datasheet for: 106402



### 3/2-way mini valve, manual, Rotating knob, NC, monostable, M5 side

3/2-way miniature valve, manual, Rotating knob, NC, monostable, M5 side, Operating pre. 0.5-10 bar, Operating temp. -10°C to 60°C. Monostable (non-latching) and bistable (latching) versions available.

Type number	512.204
Article number	106402
EAN/barcode	 4047322096317
Your price	40,58 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

Connection	M5 female thread on side
Flow rate at 6 bar and $\Delta p$ 0.5 bar	35 NI/min
Function	3/2 NC
Max. operating pressure	10 bar
Max. operating temperature	60 °C
Min. operating pressure	0.5 bar
Min. operating temperature	-10 °C
Nominal $\emptyset$	2.5 mm
Operating pressure at 6 bar	8 N
Operation	Monostable
Page No.	HK452
Pushbutton	Nickel-plated brass
Sealant	NBR
Spring	Stainless steel
Valve body	Aluminium

## Variants

Article number	Connection	Operation	Price
106402	M5 female thread on side	Monostable	40,58 € / Stk
106401	Plug-in connector Ø 4 mm on side	Monostable	41,17 € / Stk
106403	Plug-in connector Ø 4 mm on side	Bistable	40,93 € / Stk
106404	M5 female thread on side	Bistable	40,58 € / Stk

## More Pictures

