


## Datasheet for: 116436


**3/2-way blocking valve »G«, Size 400, G 3/8**

3/2-way blocking valve »G«, Mounting bracket, Padlock and silencer, Manually actuated, Size 400, G 3/8, Input pressure - 9 bar . Rotary switch can be turned 90°, lockable. The valve is used to switch off the air supply and is normally installed upstream of a pressure regulator, filter regulator or service unit. When the valve is closed, the residual air on the P2 side is discharged into the atmosphere through the relief port on the bottom.

Type number	GK 32
Article number	116436
EAN/barcode	 4047322308823
Your price	46,76 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	63.0 mm
B	134.0 mm
C	75.5 mm
D	58.5 mm
Flow rate	6200 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. input pressure	9 bar
Max. medium temperature	70 °C
Min. input pressure	0.0 bar
Page No.	WEB
Sealant	NBR
Series	G
Size	400
Thread	G 3/8
Twist knob	Plastics
Vent port	G 1/2

## Variants

Article number	Thread	Vent port	Flow rate	Size	Price
116436	G 3/8	G 1/2	6200 l/min	400	46,76 € / Stk
116434	G 3/8	G 3/8	2500 l/min	300	33,69 € / Stk
116435	G 1/2	G 3/8	2500 l/min	300	33,69 € / Stk
116433	G 1/4	G 3/8	1600 l/min	300	33,69 € / Stk
116437	G 1/2	G 1/2	6200 l/min	400	46,76 € / Stk

## More Pictures

