

Datasheet for: 110406


Push-in T-fitting, rotating, G 1/8 o., for hose exterior Ø 6 mm

Push-in T-fitting, rotating, G 1/8 o., for hose exterior Ø 6 mm, Working pressure max. 15 bar, Stainless steel 1.4404. For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	55.018-6 ES
Article number	110406
EAN/barcode	 4047322268943
Your price	51,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	6 mm
L1	42.0 mm
L2	22.5 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/8
Working pressure pulsate a/f	10.0 bar 13 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
110406	G 1/8	6 mm	13 mm	51,46 € / Stk
110405	G 1/8	4 mm	13 mm	45,69 € / Stk
110411	G 3/8	10 mm	21 mm	82,11 € / Stk
110407	G 1/8	8 mm	13 mm	59,60 € / Stk
110408	G 1/4	6 mm	16 mm	52,47 € / Stk
110409	G 1/4	8 mm	16 mm	63,67 € / Stk
110410	G 1/4	10 mm	16 mm	76,67 € / Stk
110404	M5	4 mm	9 mm	45,02 € / Stk

More Pictures

