

Datasheet for: 105837


Round cylinder, single-acting, Piston Ø 25, Stroke 10, G 1/8

Round cylinder, ISO 6432, single-acting, Magnet, Piston Ø 25, Stroke 10, G 1/8, Working pressure max. 10 bar, Temp. -10°C to 80°C. Single and double-acting cylinders, with magnetic piston. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Type number	1.EM.25010
-------------	------------

Article number	105837
----------------	--------

EAN/barcode



4047322011020

Your price	51,75 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Design	Flanged joint between stainless steel barrel and heads
Jacket	Stainless steel 1.4301
Max. temperature range	80 °C
Max. working pressure	10 bar
Min. set pressure	0.6 bar
Min. temperature range	-10 °C
Page No.	HK393
Piston	Synthetic (acetal) resin
Piston rod	C45 steel, hard chrome-plated
Piston rod thread	M10x1.25
Piston Ø	25 mm
Sealant	NBR
Stroke	10 mm

Variants

Article number	Piston Ø	Stroke	Connection	Piston rod thread	Price
105837	25 mm	10 mm	G 1/8	M10x1.25	51,75 € / Stk
105822	8 mm	10 mm	M5	M4	37,18 € / Stk
105823	8 mm	25 mm	M5	M4	37,40 € / Stk
105824	8 mm	50 mm	M5	M4	37,87 € / Stk
105825	10 mm	10 mm	M5	M4	37,87 € / Stk
105826	10 mm	25 mm	M5	M4	38,46 € / Stk
105827	10 mm	50 mm	M5	M4	39,05 € / Stk
105828	12 mm	10 mm	M5	M6	40,34 € / Stk
105829	12 mm	25 mm	M5	M6	40,81 € / Stk
105830	12 mm	50 mm	M5	M6	41,52 € / Stk
105831	16 mm	10 mm	M5	M6	39,53 € / Stk
105832	16 mm	25 mm	M5	M6	40,58 € / Stk
105833	16 mm	50 mm	M5	M6	42,45 € / Stk
105834	20 mm	10 mm	G 1/8	M8	46,94 € / Stk
105835	20 mm	25 mm	G 1/8	M8	47,53 € / Stk
105836	20 mm	50 mm	G 1/8	M8	48,93 € / Stk
105838	25 mm	25 mm	G 1/8	M10x1.25	53,06 € / Stk
105839	25 mm	50 mm	G 1/8	M10x1.25	55,30 € / Stk

More Pictures

