


Datasheet for: 115969


5/3-way valve, Manual lever »4H« Middle position closed, G 1/4

5/3-way valve, Manual lever actuation »4H« Middle position closed, engaging, G 1/4, Operating press. 0-8 bar, Temp. -20°C to 70°C . 5/2- and 5/3-way valves - Manually operated -

Type number	514.2001
Article number	115969
EAN/barcode	 4047322311953
Your price	43,18 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Exhaust connection	G 1/8
Flow rate	850 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/3
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Stable, mid-position closed
Page No.	HK460
Page No. AS	AS082
Size	200
Symbol	17
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
115969	G 1/4	G 1/8	850 l/min	200	43,18 € / Stk
115968	G 1/8	G 1/8	750 l/min	200	43,18 € / Stk
115970	G 1/4	G 1/4	1300 l/min	300	57,85 € / Stk
115971	G 3/8	G 1/4	1500 l/min	300	57,85 € / Stk

More Pictures

