


Datasheet for: 116098



3/2-way valve, electropneumatic »3V« monostable, NO, 230 V, 50 Hz

3/2-way valve, electropneumatic, »3V«, monostable, NO, G 3/8, 230 V, 50 Hz, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C . 3/2-way pilot valves - Electro-pneumatic -

Type number	517.1105
Article number	116098
EAN/barcode	 4047322310178
Your price	64,72 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 3/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 3/8
Flow rate	1500 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NO
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Monostable
Page No.	HK467
Page No. AS	AS086
Protection IP	IP 65
Size	300
Symbol	32
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116098	G 3/8	G 3/8	230 V, 50 Hz	1500 l/min	300	64,72 € / Stk
116094	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	55,28 € / Stk
116093	M5	M5	230 V, 50 Hz	300 l/min	100	55,28 € / Stk
116092	G 3/8	G 3/8	24 V DC	1500 l/min	300	64,72 € / Stk
116091	G 1/4	G 1/4	24 V DC	1300 l/min	300	64,72 € / Stk
116088	G 1/8	G 1/8	24 V DC	500 l/min	100	55,28 € / Stk
116087	M5	M5	24 V DC	300 l/min	100	55,28 € / Stk
116089	G 1/8	G 1/8	24 V DC	750 l/min	200	57,96 € / Stk
116090	G 1/4	G 1/4	24 V DC	850 l/min	200	57,96 € / Stk
116095	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	57,96 € / Stk
116096	G 1/4	G 1/4	230 V, 50 Hz	850 l/min	200	57,96 € / Stk
116097	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	64,72 € / Stk

More Pictures

