


Datasheet for: 116104


3/2-way valve, electropneumatic, »3V«, monostable, NC, 24 V DC

3/2-way valve, electropneumatic, »3V«, monostable, NC, G 3/8, 24 V DC, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C . 3/2-way pilot valves - Electro-pneumatic -

Type number	517.1205
Article number	116104
EAN/barcode	 4047322310239
Your price	64,72 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 3/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 3/8
Flow rate	1500 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NC
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Monostable
Page No.	HK467
Page No. AS	AS086
Protection IP	IP 65
Size	300
Symbol	33
Valve body	Aluminium alloy
Voltage	24 V DC

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116104	G 3/8	G 3/8	24 V DC	1500 l/min	300	64,72 € / Stk
116099	M5	M5	24 V DC	300 l/min	100	55,28 € / Stk
116100	G 1/8	G 1/8	24 V DC	500 l/min	100	55,28 € / Stk
116102	G 1/4	G 1/4	24 V DC	850 l/min	200	57,96 € / Stk
116110	G 3/8	G 3/8	230 V, 50 Hz	1500 l/min	300	64,72 € / Stk
116109	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	64,72 € / Stk
116105	M5	M5	230 V, 50 Hz	300 l/min	100	55,28 € / Stk
116101	G 1/8	G 1/8	24 V DC	750 l/min	200	57,96 € / Stk
116103	G 1/4	G 1/4	24 V DC	1300 l/min	300	64,72 € / Stk
116106	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	55,28 € / Stk
116107	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	57,96 € / Stk
116108	G 1/4	G 1/4	230 V, 50 Hz	850 l/min	200	57,96 € / Stk

More Pictures

