


## Datasheet for: 100355


**Filter regulator »multifix-mini«, Metal container, G 1/8, 0.5-10**

Filter regulator »multifix-mini«, Metal container, press. gauge, 5  $\mu\text{m}$ , G 1/8, Input pressure max. 16 bar, Control range 0.5-10 bar . Reversible diaphragm pressure regulators, independent of inlet pressure, with secondary ventilation, in combination with a centrifugal separator. The pressure setting can be locked by pressing in the handwheel.

Type number	C 05 M
Article number	100355
EAN/barcode	 4047322123907
Your price	52,07 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	40.0 mm
B	162.0 mm
Bowl	Metal container
C	63.0 mm
Condensate drain	Semi-automatic
D	99.0 mm
DN	5.0
Filter rating	5.0 $\mu\text{m}$
Flow rate	1450 l/min
Flow rate measurement	At $P_1 = 10 \text{ bar}$ , $P_2 = 6.3 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK067
Pressure gauge display max.	16.0 bar

Pressure gauge display min. Sealant Series Spring bonnet Thread	0.0 bar NBR multifix-mini POM-brass G 1/8
--	---

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Flow rate</i>	<i>Price</i>
100355	G 1/8	1450 l/min	52,07 € / Stk
100356	G 1/4	1450 l/min	52,07 € / Stk

## More Pictures

