


Datasheet for: 135178


Push-in T-fitting, rotating, G 1/4 o., for hose exterior Ø 8 mm

Push-in T-fitting, rotating, G 1/4 o., for hose exterior Ø 8 mm, Working pressure max. 20 bar, Stainless steel 1.4404. For use in more aggressive environments and corrosive media.

Type number	855.014-8 ES
Article number	135178
EAN/barcode	 4047322493864
Your price	57,64 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	8 mm
L1	46.4 mm
L2	29.0 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	20 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	HK720
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/4
Working pressure pulsate a/f	10.0 bar 17 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
135178	G 1/4	8 mm	17 mm	57,64 € / Stk
135181	G 3/8	8 mm	21 mm	82,64 € / Stk
135188	G 1/2	16 mm	27 mm	170,74 € / Stk
135172	M5	4 mm	11 mm	48,44 € / Stk
135173	G 1/8	4 mm	14 mm	41,45 € / Stk
135174	G 1/8	6 mm	14 mm	44,81 € / Stk
135180	G 1/4	12 mm	19 mm	126,24 € / Stk
135186	G 1/2	12 mm	27 mm	134,42 € / Stk
135175	G 1/8	8 mm	14 mm	54,31 € / Stk
135182	G 3/8	10 mm	21 mm	90,94 € / Stk
135185	G 1/2	10 mm	27 mm	106,19 € / Stk
135179	G 1/4	10 mm	17 mm	84,79 € / Stk
135183	G 3/8	12 mm	21 mm	111,18 € / Stk
135187	G 1/2	14 mm	27 mm	156,82 € / Stk
135184	G 3/8	14 mm	22 mm	145,61 € / Stk
135176	G 1/4	4 mm	17 mm	55,44 € / Stk
135177	G 1/4	6 mm	17 mm	46,11 € / Stk

More Pictures

