


Datasheet for: 106857


3/2-way solenoid valve silenced venting, G 1/8, NO, hose 8

3/2-way solenoid valve »lineonline« silenced venting, Hose - thread, G 1/8, Hose Ø 8, NO, 24 V DC, Operating pressure 2.5 - 7 bar . Though small in size, these valves are solenoid-piloted and feature very high performance. Each valve comes complete with a monostable manual control and LED. Exhaust can be damped with a silencer or conveyed via a pipe fitting. Function corresponds to the normal position of the valve.

Type number	485.018-8
Article number	106857
EAN/barcode	 4047322093071
Your price	64,93 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	66.4 mm
B	63.5 mm
Body	Technopolymer
Flow rate at 6.3 bar and Δp 1.0 bar	700 NI/min
For pipe Ø	8.0 mm
Function	NO
I	18.7 mm
Internal parts	Nickel-plated brass, brass, technopolymer, stainless steel
Max. operating pressure	7 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. temperature range	-20 °C
Operating voltage	24 V DC
Page No.	HK497
Pneumatic symbols	On housing
Power input	1.2 W
Sealant	NBR
Thread	G 1/8

Variants

Article number	Thread	For pipe Ø	Function	Flow rate at 6.3 bar and Δp 1.0 bar	Price
106857	G 1/8	8.0 mm	NO	700 NI/min	64,93 € / Stk
106851	G 1/8	6.0 mm	NC	380 NI/min	64,33 € / Stk
106852	G 1/8	8.0 mm	NC	700 NI/min	64,93 € / Stk
106853	G 1/4	6.0 mm	NC	380 NI/min	64,93 € / Stk
106854	G 1/4	8.0 mm	NC	700 NI/min	65,28 € / Stk
106855	G 3/8	8.0 mm	NC	700 NI/min	66,56 € / Stk
106856	G 1/8	6.0 mm	NO	380 NI/min	64,33 € / Stk
106858	G 1/4	6.0 mm	NO	380 NI/min	64,93 € / Stk
106859	G 1/4	8.0 mm	NO	700 NI/min	65,28 € / Stk
106860	G 3/8	8.0 mm	NO	700 NI/min	66,56 € / Stk

More Pictures

