


Datasheet for: 100519



Filter »multifix«, PC container, Protective cage, Size 3, G 1/2

Filter »multifix«, PC container and protective cage, 5 μm , Size 3, G 1/2, Input pressure max. 16 bar, Med./ambient temp. max. 60°C . Centrifugal separators with a sintered filter element.

Type number	F 33 S
Article number	100519
EAN/barcode	 4047322131001
Your price	64,99 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	68.8 mm
B	181.8 mm
Bowl	Polycarbonate container with protective cage
C	34.5 mm
Condensate drain	Semi-automatic
D	147.3 mm
DN	15.0
Filter rating	5.0 μm
Flow rate	4000 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK084
Series	multifix
Size	3
Thread	G 1/2

Variants

Article number	Thread	Housing	Filter rating	Flow rate	DN	Size	Price
100519	G 1/2	Die-cast zinc	5.0 μm	4000 l/min	15.0	3	64,99 € / Stk
100517	G 1/4	Die-cast zinc	5.0 μm	2100 l/min	6.0	1	40,19 € / Stk
100518	G 3/8	Die-cast zinc	5.0 μm	2100 l/min	10.0	1	40,19 € / Stk
100520	G 3/4	Die-cast zinc	5.0 μm	4000 l/min	20.0	3	64,99 € / Stk
100521	G 1	Aluminium	40.0 μm	8000 l/min	25.0	5	171,36 € / Stk
133111	G 3/4	Die-cast aluminium	5.0 μm	7800 l/min	20.0	4	133,23 € / Stk
133112	G 1	Die-cast aluminium	5.0 μm	7800 l/min	25.0	4	133,23 € / Stk

More Pictures

