


Datasheet for: 116058


5/2-way valve, Pneumatic, »4A«, monostable, G 1/2

 5/2-way valve, Pneumatic, »4A«, monostable, G 1/2,
 Operating pressure 1.5 - 8 bar, Temperature range max. 70
 °C . 5/2-way pilot valves - Pneumatic -

Type number	516.4006
Article number	116058
EAN/barcode	 4047322309615
Your price	65,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/2
Control air port	G 1/8
Exhaust connection	G 1/2
Flow rate	2000 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Operation	Monostable
Page No.	HK464
Page No. AS	AS084
Size	400
Symbol	27
Valve body	Aluminium alloy

Variants

Article number	Connection	Exhaust connection	Flow rate	Size	Price
116058	G 1/2	G 1/2	2000 l/min	400	65,07 € / Stk
116052	M5	M5	300 l/min	100	29,67 € / Stk
116053	G 1/8	G 1/8	500 l/min	100	29,67 € / Stk
116056	G 1/4	G 1/4	1300 l/min	300	41,44 € / Stk
116054	G 1/8	G 1/8	750 l/min	200	32,35 € / Stk
116057	G 3/8	G 1/4	1500 l/min	300	41,44 € / Stk
116055	G 1/4	G 1/8	850 l/min	200	32,35 € / Stk

More Pictures

