


Datasheet for: 116599



2/2-way solenoid valve »2KW« NO, directly operated, 24 V DC

2/2-way solenoid valve »2KW«, Brass, NO, directly operated, 24 V DC, Medium temperature max. 80 °C / 90 °C, G 1/8, PN - 20 bar . Standard series available in two different versions:
 -Directly operated -Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media. Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

Type number	MVH 1531
Article number	116599
EAN/barcode	 4047322324991
Your price	52,64 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	40.0 mm
C	76.0 mm
DN	1.5
Housing	Brass
Internal parts	Stainless steel
Max. operating pressure	20 bar
Page No.	HK325
Page No. AS	AS047
Protection IP	IP 65
Sealant	FPM
Standard thread	G thread acc. to DIN EN ISO 228-1
Thread	G 1/8
Type	2
Valve seat	Brass

Variants

Article number	Thread	DN	Price
116599	G 1/8	1.5	52,64 € / Stk
116603	G 3/8	3	74,84 € / Stk
116601	G 1/4	1.5	52,64 € / Stk
116605	G 1/2	3	74,84 € / Stk

More Pictures

