


Datasheet for: 116107



3/2-way valve, electropneumatic »3V« monostable, NC, 230 V, 50 Hz

3/2-way valve, electropneumatic, »3V«, monostable, NC, G 1/8, 230 V, 50 Hz, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C . 3/2-way pilot valves - Electro-pneumatic -

Type number	517.1302
Article number	116107
EAN/barcode	 4047322310260
Your price	57,96 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/8
Flow rate	750 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	3/2 NC
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Monostable
Page No.	HK467
Page No. AS	AS086
Protection IP	IP 65
Size	200
Symbol	33
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116107	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	57,96 € / Stk
116099	M5	M5	24 V DC	300 l/min	100	55,28 € / Stk
116100	G 1/8	G 1/8	24 V DC	500 l/min	100	55,28 € / Stk
116102	G 1/4	G 1/4	24 V DC	850 l/min	200	57,96 € / Stk
116110	G 3/8	G 3/8	230 V, 50 Hz	1500 l/min	300	64,72 € / Stk
116109	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	64,72 € / Stk
116104	G 3/8	G 3/8	24 V DC	1500 l/min	300	64,72 € / Stk
116105	M5	M5	230 V, 50 Hz	300 l/min	100	55,28 € / Stk
116101	G 1/8	G 1/8	24 V DC	750 l/min	200	57,96 € / Stk
116103	G 1/4	G 1/4	24 V DC	1300 l/min	300	64,72 € / Stk
116106	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	55,28 € / Stk
116108	G 1/4	G 1/4	230 V, 50 Hz	850 l/min	200	57,96 € / Stk

More Pictures

