


Datasheet for: 112942

Fitting elbow 98, IT/ET, Rp 2 1/2, black malleable cast iron


Fitting elbow 98, conical sealing, IT/ET, Rp 2 1/2, Operating temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galva. . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFV 98-212
Article number	112942
EAN/barcode	 4047322396141
Your price	65,39 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK857
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread 1	Rp 2 1/2
Thread 2	R 2 1/2

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>Price</i>
112942	Rp 2 1/2	R 2 1/2	65,39 € / Stk
112938	Rp 1	R 1	9,88 € / Stk
112940	Rp 1 1/2	R 1 1/2	19,76 € / Stk
112937	Rp 3/4	R 3/4	8,44 € / Stk
112941	Rp 2	R 2	31,26 € / Stk
112936	Rp 1/2	R 1/2	6,28 € / Stk
112939	Rp 1 1/4	R 1 1/4	16,17 € / Stk
112935	Rp 1/4	R 1/4	7,15 € / Stk