


Datasheet for: 101001


Special filter »Standard« Metal container, 0.01 μm , Size 1, G 3/8

Special filter »Standard« with metal container, 0.01 μm , Size 1, G 3/8, Input pressure max. 25 bar, Med. / ambient temp. max. 50°C . For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

| | |
|----------------|--|
| Type number | 674 M |
| Article number | 101001 |
| EAN/barcode |  4047322111676 |
| Your price | 65,47 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|---|
| A | 48.0 mm |
| Bowl | Metal container |
| C | 14.0 mm |
| Condensate drain | Manuel |
| D | 133.5 mm |
| DN | 6.0 |
| Efficiency | 99.999 % |
| Filter rating | 0.01 μm |
| Flow rate | 380 l/min |
| Flow rate measurement | At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| H | 38.0 mm |
| Housing | Die-cast zinc, painted silver |
| Max. ambient temperature | 50 °C |
| Max. input pressure | 25 bar |
| Max. medium temperature | 50 °C |
| Page No. | HK127 |
| Series | Standard |
| Size | 1 |
| Thread | G 3/8 |

Variants

| Article number | Thread | Flow rate | Size | DN | Price |
|----------------|--------|------------|------|------|----------------|
| 101001 | G 3/8 | 380 l/min | 1 | 6.0 | 65,47 € / Stk |
| 101000 | G 1/4 | 380 l/min | 1 | 6.0 | 56,27 € / Stk |
| 101002 | G 3/8 | 720 l/min | 2 | 10.0 | 79,44 € / Stk |
| 101003 | G 1/2 | 1250 l/min | 3 | 15.0 | 110,66 € / Stk |
| 101004 | G 3/4 | 7000 l/min | 4 | 20.0 | 322,79 € / Stk |
| 101005 | G 1 | 7000 l/min | 4 | 25.0 | 349,81 € / Stk |

More Pictures

