


Datasheet for: 101025


Mist oiler »Standard«, PC container, Prot. cage, Size 3, G 1/2

Mist oiler »Standard«, PC container, protective cage, Size 3, G 1/2, Input pressure max. 16 bar, Medium / ambient temp. max. 60 °C . Proportional lubricators, oil can be filled under pressure.

Type number	760 S
Article number	101025
EAN/barcode	 4047322117388
Your price	75,14 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	79.0 mm
Bowl	Polycarbonate container with protective cage
C	55.0 mm
D	157.0 mm
DN	15.0
Flow rate	4000 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK128
Sealant	NBR
Series	Standard
Sight dome	PA
Size	3
Thread	G 1/2

Variants

Article number	Thread	Flow rate	Size	DN	Price
101025	G 1/2	4000 l/min	3	15.0	75,14 € / Stk
101022	G 1/4	1200 l/min	1	6.0	46,25 € / Stk
101023	G 3/8	1200 l/min	1	6.0	46,25 € / Stk
101024	G 3/8	2400 l/min	2	10.0	75,14 € / Stk
101026	G 3/4	9000 l/min	3	20.0	123,94 € / Stk
101027	G 1	9000 l/min	3	25.0	123,94 € / Stk
101028	G 1 1/4	9000 l/min	4	40.0	226,92 € / Stk
101029	G 1 1/2	9000 l/min	4	45.0	226,92 € / Stk

More Pictures

