

Datasheet for: 134061



Pushbutton safety coupling I.D.5.5, rotating, Alu, Sleeve I.D. 9

Pushbutton safety coupling I.D. 5.5, ARO 210, rotating, Alu, Sleeve I.D. 9, Operating pressure max. 12 bar, Temp. -20°C to 70°C. High-quality, robust and durable, one-hand quick disconnect safety couplings. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive.

Type number	244.32-D-A
Article number	134061
EAN/barcode	 4047322483889
Your price	59,52 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 9
DN	5.5
Flow rate	1080 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 1$ bar
Housing	Anodised aluminium
Internal parts	Stainless steel 1.4404
Length	93.5 mm
Max. ambient temperature	70 °C
Max. medium temperature	70 °C
Max. operating pressure	12 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK575
Page No. SK	SK059
Plug profile	acc. ARO 210

Pushbutton	Hardened, galvanised steel
Sealant	NBR
Threaded piece	Nickel-plated brass
Valve	Hardened, galvanised steel
a/f	21 mm

Variants

Article number	Connection	Price
134061	I.D. 9	59,52 € / Stk
134060	I.D. 6	59,52 € / Stk
134062	I.D. 13	59,52 € / Stk

More Pictures

