


Datasheet for: 110407



Push-in T-fitting, rotating, G 1/8 o., for hose exterior Ø 8 mm

Push-in T-fitting, rotating, G 1/8 o., for hose exterior Ø 8 mm, Working pressure max. 15 bar, Stainless steel 1.4404 . For use with aggressive media and in areas susceptible to corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

Type number	55.018-8 ES
Article number	110407
EAN/barcode	 4047322268950
Your price	59,60 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	8 mm
L1	43.0 mm
L2	22.5 mm
Material	Stainless steel 1.4404
Max. medium temperature	150 °C
Max. operating temperature	150 °C
Max. working pressure	15 bar
Min. medium temperature	-20 °C
Min. operating temperature	-20 °C
Page No.	WEB
Standard thread	DIN EN ISO 228-1
Suitable pipe materials	PVDF, PTFE, PA, PU
Thread	G 1/8
Working pressure pulsate a/f	10.0 bar 13 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
110407	G 1/8	8 mm	13 mm	59,60 € / Stk
110405	G 1/8	4 mm	13 mm	45,69 € / Stk
110411	G 3/8	10 mm	21 mm	82,11 € / Stk
110406	G 1/8	6 mm	13 mm	51,46 € / Stk
110408	G 1/4	6 mm	16 mm	52,47 € / Stk
110409	G 1/4	8 mm	16 mm	63,67 € / Stk
110410	G 1/4	10 mm	16 mm	76,67 € / Stk
110404	M5	4 mm	9 mm	45,02 € / Stk

More Pictures

