

Datasheet for: 103504



Ball valve high pressure design, Lightweight series, M30x2

Ball valve, High pressure design, Lightweight series, Steel, Operating temp. -10 °C to 100 °C, M30x2, DN 20, PN max. 420 bar . For liquid and lubricating media. Available versions:
 - For solderless tube fittings acc. to DIN 2353, lightweight series acc. to ISO 8434-1. - For solderless tube fittings acc. to DIN 2353, heavy-duty series acc. to ISO 8434-1. - With female pipe thread acc. to DIN ISO 228-1 (BSP).

Type number	392.07
Article number	103504
EAN/barcode	 4047322081825
Your price	59,64 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	187.0 mm
B	121.0 mm
Ball	Hard-chrome plated steel
Bore inball	Full bore
Control ball seal	POM
DN	20.0
For tube O.D.	22L mm
Housing	Steel
L	99.0 mm
Max. operating pressure	420 bar
Max. operating temperature	100 °C
Min. operating temperature	-10 °C
Page No.	HK298
Selector shaft	Steel
Selector shaft seal	NBR
Thread	M30x2

Variants

Article number	Thread	Max. operating pressure	DN	For tube O.D.	Price
103504	M30x2	420 bar	20.0	22L mm	59,64 € / Stk
103498	M12x1.5	500 bar	4.0	6L mm	25,52 € / Stk
103499	M14x1.5	500 bar	6.0	8L mm	24,11 € / Stk
103500	M16x1.5	500 bar	8.0	10L mm	26,32 € / Stk
103501	M18x1.5	500 bar	10.0	12L mm	27,73 € / Stk
103502	M22x1.5	500 bar	12.0	15L mm	30,52 € / Stk
103503	M26x1.5	420 bar	16.0	18L mm	49,51 € / Stk
103505	M36x2	420 bar	25.0	28L mm	74,31 € / Stk

More Pictures

