


Datasheet for: 114478


Low noise flat nozzle, G 1/4 ET, Nozzle width 21.5 mm

Low noise flat nozzle, G 1/4 ET, Safety nozzle general applications, nickel-plated brass, Length 100.0 mm, Nozzle width 21.5 mm . If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

Type number	30.401
Article number	114478
EAN/barcode	 4047322247917
Your price	67,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Diagram	11
Length	100.0 mm
Material	Nickel-plated brass
Nozzle type	Low-noise flat nozzle
Nozzle width	21.5 mm
Page No.	HK966
Page No. SF	SF105
Thread	G 1/4 ET

Variants

Article number	Thread	Material	Length	Nozzle width	Price
114478	G 1/4 ET	Nickel-plated brass	100.0 mm	21.5 mm	67,22 € / Stk
114481	G 1/4 ET	Nickel-plated brass	100.0 mm	21.0 mm	68,02 € / Stk
114479	G 3/8 ET	Nickel-plated brass	100.0 mm	29.0 mm	82,25 € / Stk

Variants

<i>Article number</i>	<i>Thread</i>	<i>Material</i>	<i>Length</i>	<i>Nozzle width</i>	<i>Price</i>
114482	G 3/8 ET	Nickel-plated brass	100.0 mm	29.0 mm	87,01 € / Stk
114480	G 3/8 ET	Galvanised steel	50.0 mm	16.5 mm	53,58 € / Stk