

Datasheet for: 100923



Filter regulator »Standard«, PC container, 5 µm, Size 1, G 3/8

Filter regulator »Standard«, PC container, press. gauge, 5 µm, Size 1, G 3/8, Input pressure max. 16 bar, Control range 0.5-10 bar. Reversible diaphragm pressure regulators, independent of inlet pressure, with selfrelieving design, combined with a centrifugal separator.

Type number	578.030 K-HA
Article number	100923
EAN/barcode	 4047322338066
Your price	54,68 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	54.0 mm
Bowl	Polycarbonate container
C	106.5 mm
Condensate drain	Semi-automatic
D	129.7 mm
DN	8.0
F	62.0 mm
Filter rating	5.0 µm
Flow rate	900 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK123
Pressure gauge display max.	16.0 bar

Pressure gauge
 display min.
 Sealant
 Series
 Size
 Thread

0.0 bar
 NBR
 Standard
 1
 G 3/8

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	Price
100923	G 3/8	Die-cast zinc, painted silver	5.0 μm	900 l/min	1	54,68 € / Stk
100922	G 1/4	Die-cast zinc, painted silver	5.0 μm	900 l/min	1	54,68 € / Stk
100924	G 3/8	Die-cast zinc, painted silver	40.0 μm	1500 l/min	2	94,83 € / Stk
100926	G 3/4	Aluminium, painted silver	40.0 μm	7000 l/min	4	266,70 € / Stk
100927	G 1	Aluminium, painted silver	40.0 μm	7000 l/min	4	266,70 € / Stk
100925	G 1/2	Die-cast zinc, painted silver	5.0 μm	3000 l/min	3	94,83 € / Stk
174092	G 3/4	Aluminium, painted silver	40.0 μm	12000 l/min	4	266,70 € / Stk
174093	G 1	Aluminium, painted silver	40.0 μm	12000 l/min	4	266,70 € / Stk

More Pictures

