

Datasheet for: 116135


5/2-way valve, electropneumatic, »4V«, monostable, 230 V, 50 Hz

5/2-way valve, electropneumatic, »4V«, monostable, G 3/8, 230 V, 50 Hz, Operating pressure 1.5 - 8 bar, Temp. -20 °C to 70 °C. 5/2-way pilot valves - Electro-pneumatic -

Type number	517.2105
Article number	116135
EAN/barcode	 4047322310604
Your price	67,50 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 3/8
Electrical connection	Connector Type B acc. to ISO 4400
Exhaust connection	G 1/4
Flow rate	1500 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Manual control	latching/non-latching
Max. operating pressure	8 bar
Max. temperature range	70 °C
Min. operating pressure	1.5 bar
Min. temperature range	-20 °C
Min. working pressure	1.5 bar
Operation	Monostable
Page No.	HK468
Page No. AS	AS087
Protection IP	IP 65
Size	300
Symbol	35
Valve body	Aluminium alloy
Voltage	230 V, 50 Hz

Variants

Article number	Connection	Exhaust connection	Voltage	Flow rate	Size	Price
116135	G 3/8	G 1/4	230 V, 50 Hz	1500 l/min	300	67,50 € / Stk
116129	G 1/2	G 1/2	24 V DC	2000 l/min	400	67,50 € / Stk
116130	M5	M5	230 V, 50 Hz	300 l/min	100	59,37 € / Stk
116125	G 1/8	G 1/8	24 V DC	750 l/min	200	60,53 € / Stk
116127	G 1/4	G 1/4	24 V DC	1300 l/min	300	67,50 € / Stk
116128	G 3/8	G 1/4	24 V DC	1500 l/min	300	67,50 € / Stk
116134	G 1/4	G 1/4	230 V, 50 Hz	1300 l/min	300	67,50 € / Stk
116123	M5	M5	24 V DC	300 l/min	100	59,37 € / Stk
116124	G 1/8	G 1/8	24 V DC	500 l/min	100	59,37 € / Stk
116131	G 1/8	G 1/8	230 V, 50 Hz	500 l/min	100	59,37 € / Stk
116132	G 1/8	G 1/8	230 V, 50 Hz	750 l/min	200	60,53 € / Stk
116136	G 1/2	G 1/2	230 V, 50 Hz	2000 l/min	400	67,50 € / Stk
116126	G 1/4	G 1/8	24 V DC	850 l/min	200	60,53 € / Stk
116133	G 1/4	G 1/8	230 V, 50 Hz	850 l/min	200	60,53 € / Stk

More Pictures

