Datasheet for: 106696



Intermediate plate for valve terminal HDM, separated air intake

Intermediate plate for valve terminal HDM with separated air intake (for multi-pressure systems, 2+4 are separately pressurised) . These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

Type number	7
Article number	106696
EAN/barcode	4047322286794
Your price	67,63 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Function	With separate pilots (2+4 are separately pressurised)
Manual control	latching
Max. temperature range	60 °C
Min. temperature range	-10 °C
Page No.	HK484
Piloting	Max. 16 (e.g. 16 spring return valves)
Power input	0.6 W per pilot
Protection IP	IP 65

Variants

Article number	Function	Price
106696	With separate pilots (2+4 are separately pressurised)	67,63 € / Stk
106695	With additional pilots and exhausts	71,52 € / Stk
106697	With separate exhausts (2+4 are separately exhausted)	62,11 € / Stk