

## Datasheet for: 135913



### Stainless steel ball valve, length acc. to DIN 3202-M3, G 3/4

Stainless steel ball valve, 3-piece, length acc. to DIN 3202-M3, G 3/4, DN 20, Operating temp. -20 °C to 180 °C, PN max. 63 bar .

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | 3390.04                                                                                            |
| Article number | 135913                                                                                             |
| EAN/barcode    | <br>4047322501552 |
| Your price     | 59,81 € / Stk                                                                                      |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                            |                                                          |
|----------------------------|----------------------------------------------------------|
| A                          | 143.0 mm                                                 |
| B                          | 79.0 mm                                                  |
| Ball                       | Stainless steel 1.4401                                   |
| Ball seal                  | PTFE (15 % glass fibre reinforced)                       |
| DN                         | 20.0                                                     |
| Hand lever                 | Stainless steel 1.4301, with plastic coating             |
| Housing                    | Stainless steel 1.4408                                   |
| ISO 5211                   | F 03 / F 04                                              |
| L                          | 80.0 mm                                                  |
| Max. operating temperature | 180 °C                                                   |
| Min. operating temperature | -20 °C                                                   |
| PN                         | 63 bar                                                   |
| Page No.                   | HK278                                                    |
| Standard thread            | G thread acc. to DIN EN ISO 228-1, flange plate ISO 5211 |
| Stem seal                  | PTFE                                                     |
| Thread                     | G 3/4                                                    |

## Variants

| Article number | Thread  | DN   | PN     | Price          |
|----------------|---------|------|--------|----------------|
| 135913         | G 3/4   | 20.0 | 63 bar | 59,81 € / Stk  |
| 135916         | G 1 1/2 | 38.0 | 63 bar | 140,60 € / Stk |
| 135910         | G 1/4   | 11.6 | 63 bar | 38,20 € / Stk  |
| 135911         | G 3/8   | 12.5 | 63 bar | 38,20 € / Stk  |
| 135915         | G 1 1/4 | 32.0 | 63 bar | 107,71 € / Stk |
| 135912         | G 1/2   | 15.0 | 63 bar | 48,65 € / Stk  |
| 135917         | G 2     | 50.0 | 63 bar | 201,94 € / Stk |
| 135914         | G 1     | 25.0 | 63 bar | 81,61 € / Stk  |
| 135919         | G 3     | 76.0 | 40 bar | 637,50 € / Stk |
| 135918         | G 2 1/2 | 64.0 | 40 bar | 469,70 € / Stk |

## More Pictures

