

## Datasheet for: 116590


**2/2-way solenoid valve »2S« NC, directly operated, 24 V DC, G 1/2**

2/2-way solenoid valve »2S«, Stainless steel, NC, directly operated, 24 V DC, Medium temp. max. 80 °C/90 °C, G 1/2, PN - 30 bar . Standard series available in two different versions: -Directly operated -Pilot-operated Connector socket, form A acc. to ISO 4400, for all valves with a G 3/8 or G 1/2 thread except valve types 3 and 4. Special connector socket (similar to form B) for all valves with a G 1/8 or G 1/4 thread except valve types 3 and 4. Medium temperature max. 80 °C when used with water or oils, max. 90 °C when used with air.

|             |             |
|-------------|-------------|
| Type number | MVH 1514 ES |
|-------------|-------------|

|                |        |
|----------------|--------|
| Article number | 116590 |
|----------------|--------|

|             |  |
|-------------|--|
| EAN/barcode | <br>4047322323949 |
|-------------|--|

|            |               |
|------------|---------------|
| Your price | 67,68 € / Stk |
|------------|---------------|

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                         |                                   |
|-------------------------|-----------------------------------|
| A                       | 85.0 mm                           |
| B                       | 52.0 mm                           |
| C                       | 87.0 mm                           |
| DN                      | 3                                 |
| Housing                 | Stainless steel 1.4301            |
| Internal parts          | Stainless steel                   |
| Max. operating pressure | 30 bar                            |
| Page No.                | HK329                             |
| Page No. AS             | AS049                             |
| Protection IP           | IP 65                             |
| Sealant                 | FPM                               |
| Standard thread         | G thread acc. to DIN EN ISO 228-1 |
| Thread                  | G 1/2                             |
| Type                    | 1                                 |
| Valve seat              | Stainless steel 1.4301            |

## Variants

| Article number | Thread | DN  | Price         |
|----------------|--------|-----|---------------|
| 116590         | G 1/2  | 3   | 67,68 € / Stk |
| 116584         | G 1/8  | 1.5 | 48,53 € / Stk |
| 116586         | G 1/4  | 1.5 | 48,53 € / Stk |
| 116588         | G 3/8  | 3   | 67,68 € / Stk |

## More Pictures

