


## Datasheet for: 113489

**Spiral hose coupling set, PUR, Hose Ø 10x6.5, Length 6.0 m**


Spiral hose coupling set I.D. 7.6, PUR, Medium / ambient temperature -20 °C to 60 °C, Hose Ø 10x6.5, PN max. 10 bar, Length 6 m . Spiral or straight polyurethane hose, completely assembled with DN 7.6 safety coupling and steel plugs. Coupling Safety coupling made of steel / nickel-plated brass for high flow rates, specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. Polyurethane hose Extremely flexible spiral hose with excellent kink resistance and insensitive to dirt. Combines high tear, tensile and impact strength with a long service life and optimal ageing qualities. This hose is additionally characterised by outstanding resistance to abrasion and resistance to UV. Not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1.

Type number	SP 246-106
Article number	113489
EAN/barcode	 4047322206495
Your price	75,58 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Coil diameter	52 mm
Hose size	10x6.5 mm
Material	Polyurethane (PUR)
Max. ambient temperature	60 °C
Max. medium temperature	60 °C
Max. operating pressure	10 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK901
Page No. SK	SK093
Service length max.	6.0 m

## Variants

<i>Article number</i>	<i>Coil diameter</i>	<i>Hose size</i>	<i>Service length max.</i>	<i>Price</i>
113489	52 mm	10x6.5 mm	6.0 m	75,58 € / Stk
113487	52 mm	10x6.5 mm	2.0 m	53,50 € / Stk
113488	52 mm	10x6.5 mm	4.0 m	64,76 € / Stk
113490	52 mm	10x6.5 mm	8.0 m	86,50 € / Stk
113491	65 mm	12x8 mm	2.0 m	61,19 € / Stk
113492	65 mm	12x8 mm	4.0 m	77,68 € / Stk
113493	65 mm	12x8 mm	6.0 m	100,32 € / Stk
113494	65 mm	12x8 mm	8.0 m	110,22 € / Stk