


Datasheet for: 124767


Filter »variobloc«, PC container, Protective cage, Size 2, G 1/2

Filter »variobloc«, Polycarbonate container and protective cage, Size 2, G 1/2, Input pressure max. 16 bar, Manual bleeder valve . Centrifugal separators with a sintered filter element. Filtration takes place in a 2-stage process comprising cyclone separation (condensate) and a PE filter element (particles). Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VF 24 S
Article number	124767
EAN/barcode	 4047322397117
Your price	67,82 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	70.0 mm
B	202.0 mm
Bowl	Polycarbonate container with protective cage
C	26.0 mm
Condensate drain	Manual
Filter rating	40.0 μm
Flow rate	3200 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	WEB
Sealant	NBR
Series	variobloc
Size	2
Thread	G 1/2

Variants

Article number	Thread	Flow rate	Size	Price
124767	G 1/2	3200 l/min	2	67,82 € / Stk
124773	G 1	3500 l/min	2	102,17 € / Stk
124763	G 1/4	1800 l/min	1	46,58 € / Stk
124770	G 3/4	3500 l/min	2	67,82 € / Stk
124765	G 3/8	2000 l/min	1	46,58 € / Stk

More Pictures

