


Datasheet for: 106419


3/2-way valve man. short wing lever, NC monost. G1/8, valve pos.2

3/2-way valve, manual, Rotating lever, NC, monostable, Connection G 1/8, Operating pre. 2.5-10 bar, Operating temp. -10°C to 60°C .

Type number	515.401
Article number	106419
EAN/barcode	 4047322205375
Your price	68,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/8
Flow rate at 6 bar and Δp 0.5 bar	400 NI/min
Flow rate at 6 bar and Δp 1.0 bar	550 NI/min
Function	3/2 NC
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Monostable
Page No.	HK455
Piston	Aluminium
Sealant	NBR
Spring	Special steel
Symbol	5
Valve body	Aluminium
Valve positions	2

Variants

<i>Article number</i>	<i>Symbol</i>	<i>Operation</i>	<i>Valve positions</i>	<i>Price</i>
106419	5	Monostable	2	68,22 € / Stk
106420	6	Bistable	2	68,22 € / Stk
106421	7	Monostable	3	69,51 € / Stk
106422	8	Bistable	3	69,51 € / Stk

More Pictures

