


Datasheet for: 115989


5/2-way valve, Manually actuated, »M5«, Short lever,G 1/4

5/2-way valve, Manually actuated, »M5«, Short lever, monostable, G 1/4, Operating pressure - 10 bar, Temperature -20 °C to 70 °C . 5/2-way valves - Manually operated, for panel mounting -

Type number	515.2101
Article number	115989
EAN/barcode	 4047322311632
Your price	68,32 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/4
Exhaust connection	G 1/8
Flow rate	550 l/min
Flow rate measurement	At P 1 = 8 bar, P 2 = 6 bar and pressure drop $\Delta p = 1$ bar
Function	5/2
Lever/switch colour	black
Max. operating pressure	10 bar
Max. temperature range	70 °C
Min. temperature range	-20 °C
Operation	Monostable
Page No.	HK457
Page No. AS	AS080
Symbol	3
Valve body	Aluminium alloy

Variants

<i>Article number</i>	<i>Connection</i>	<i>Flow rate</i>	<i>Price</i>
115989	G 1/4	550 l/min	68,32 € / Stk
115988	G 1/8	450 l/min	39,46 € / Stk

More Pictures

