

Datasheet for: 133168


Potable water ball valve, Manual lever, IT/IT, G 2, DN 50

Potable water ball valve, Nickel-plated brass, Manual lever, IT/IT, G 2, DN 50, Operating temp. -15 °C to 110 °C, PN max. 40 bar . Brass ball valve with free flow, DVGW approved. This valve complies with the European standard EN 13828 and the working paper DVGW W 570, and is therefore approved for use with drinking water. The special ball technology prevents bacteria from forming inside the valve if it is not in use for a long period of time (i.e. the valve is absolutely safe for drinking water).

Type number	350.7708
Article number	133168
EAN/barcode	 4047322476584
Your price	68,42 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	165.0 mm
Applications	Potable water, water
B	92.4 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	50.0
DVGW approval	DIN EN 13828:2003-12, DVGW W 570
Hand lever	Aluminium
Housing	Nickel-plated brass (outside), brass (inside)
L	119.0 mm
Max. operating temperature	110 °C
Min. operating temperature	-15 °C
PN	40 bar
Page No.	HK290
Standard	
thread	Thread acc. to DIN EN ISO 228-1
Stem seal	PTFE / EPDM / HNBR
Thread	G 2
Thread material	Brass

Variants

Article number	Thread	DN	Price
133168	G 2	50.0	68,42 € / Stk
133164	G 3/4	20.0	13,88 € / Stk
133163	G 1/2	15.0	8,84 € / Stk
133165	G 1	25.0	19,85 € / Stk
133166	G 1 1/4	32.0	31,39 € / Stk
133161	G 1/4	8.0	7,33 € / Stk
133162	G 3/8	10.0	7,80 € / Stk
133167	G 1 1/2	40.0	47,88 € / Stk

More Pictures

