


Datasheet for: 101278



Flange pressure controller 200 bar, Carbon dioxide, - 20 bar

Flange pressure controller, Flange pressure 200 bar, for non-flammable gases, Gas type: Carbon dioxide, Working pressure 0-20 bar . Single-stage type of construction acc. to DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauges for the cylinder contents and working pressure.

Type number	487.41 H
Article number	101278
EAN/barcode	 4047322093347
Your price	75,87 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Cylinder connection	W 21.8 x 1/14
Gas type	Carbon dioxide
Housing	Pressed brass
Indicating range	- 200/315 bar
Max. working pressure	20 bar
Page No.	HK163

Variants

Article number	Gas type	Max. working pressure	Cylinder connection	Price
101278	Carbon dioxide	20 bar	W 21.8 x 1/14	75,87 € / Stk
101271	Oxygen	10 bar	Nut 3/4	75,87 € / Stk

Variants

<i>Article number</i>	<i>Gas type</i>	<i>Max. working pressure</i>	<i>Cylinder connection</i>	<i>Price</i>
101272	Oxygen	20 bar	Nut 3/4	75,87 € / Stk
101273	Compressed air	10 bar	5/8 male	75,87 € / Stk
101274	Compressed air	20 bar	5/8 male	75,87 € / Stk
101275	Nitrogen	10 bar	W 24.32 x 1/14	75,87 € / Stk
101276	Nitrogen	20 bar	W 24.32 x 1/14	75,87 € / Stk
101277	Carbon dioxide	10 bar	W 21.8 x 1/14	75,87 € / Stk
101279	Argon/helium	10 bar	W 21.8 x 1/14	75,87 € / Stk