

Datasheet for: 102056


Pressure gauge, robust design, G 1/2, -1 / bar, Ø 100

Pressure gauge, robust design, Connection, rear, eccentric, G 1/2, Goods class 1.0, Measurement range -1/0 bar, Ø 100 . Robust bourdon-tube pressure gauge. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Type number	600
Article number	102056
EAN/barcode	 4047322104425
Your price	76,28 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.0
Connection	G 1/2
Connection position	rear, excentrical
Diameter	100 mm
Front glass	Flat instrument glass
Housing	CrNi steel
Lower / Upper range limit	Vacuum
Max. ambient temperature	60 °C
Max. medium temperature	80 °C
Measuring element	Copper alloy
Measuring range max. bar	0.0
Measuring range min. bar	-1.0
Min. ambient temperature	-40 °C
Movement	Copper alloy
Page No.	HK206
Scale graduation in the bar area	0.02 bar
Type	212.20

Variants

<i>Article number</i>	<i>Measuring element</i>	<i>Measuring range min. bar</i>	<i>Measuring range max. bar</i>	<i>Price</i>
102056	Copper alloy	-1.0	0.0	76,28 € / Stk
102057	Copper alloy	0.0	1.0	76,28 € / Stk
102058	Copper alloy	0.0	1.6	76,28 € / Stk
102059	Copper alloy	0.0	2.5	76,28 € / Stk
102060	Copper alloy	0.0	4.0	76,28 € / Stk
102061	Copper alloy	0.0	6.0	72,81 € / Stk
102062	Copper alloy	0.0	10.0	72,81 € / Stk
102063	Copper alloy	0.0	16.0	72,81 € / Stk
102064	Copper alloy	0.0	25.0	72,81 € / Stk
102065	Copper alloy	0.0	40.0	72,81 € / Stk
102066	CrNi steel	0.0	160.0	105,66 € / Stk
102067	CrNi steel	0.0	250.0	105,66 € / Stk