

Datasheet for: 102930


2/2-solenoid valve,NC,pilot operat., 24V DC,8W,FKM,G3/8,0.1-10bar

2/2-way solenoid valve brass, NC, pilot operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 3/8, PN 0.1 - 10bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

| | |
|-------------|-----------|
| Type number | MV 1361 G |
|-------------|-----------|

| | |
|----------------|--------|
| Article number | 102930 |
|----------------|--------|

| | |
|-------------|--|
| EAN/barcode | |
|-------------|--|



4047322159180

| | |
|------------|---------------|
| Your price | 60,91 € / Stk |
|------------|---------------|

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|--|
| A | 54.0 mm |
| B | 50.0 mm |
| DN | 12.0 |
| Electrical connection | For connector socket Pg 9/Pg 11 acc. to ISO 4400 |
| Function | normally closed (NC) |
| Housing | Brass |
| Internal parts | Stainless steel |
| Max. ambient temperature | 80 °C |
| Max. medium temperature | 140 °C |
| Max. operating pressure | 10 bar |
| Min. ambient temperature | -10 °C |
| Min. medium temperature | -10 °C |
| Min. operating pressure | 0.1 bar |
| Page No. | HK322 |
| Protection IP | IP 65 (with connector socket fitted) |
| Sealant | FPM |
| Thread | G 3/8 |
| Type | 3 |
| Valve seat | Brass |

Variants

| Article number | Thread | Min. operating pressure | Max. operating pressure | Max. medium temperature | DN | Sealant | Price |
|----------------|---------|-------------------------|-------------------------|-------------------------|------|---------|----------------|
| 102930 | G 3/8 | 0.1 bar | 10 bar | 140 °C | 12.0 | FPM | 60,91 € / Stk |
| 102931 | G 3/8 | 0.1 bar | 10 bar | 90 °C | 12.0 | NBR | 57,55 € / Stk |
| 102932 | G 3/8 | 0.2 bar | 16 bar | 90 °C | 13.0 | NBR | 64,30 € / Stk |
| 102933 | G 3/8 | 0.2 bar | 16 bar | 140 °C | 13.0 | FPM | 67,67 € / Stk |
| 102934 | G 3/8 | 0.2 bar | 12 bar | 90 °C | 13.0 | NBR | 54,52 € / Stk |
| 102935 | G 3/8 | 0.2 bar | 12 bar | 140 °C | 13.0 | FPM | 57,55 € / Stk |
| 102936 | G 1/2 | 0.1 bar | 10 bar | 140 °C | 12.0 | FPM | 60,91 € / Stk |
| 102937 | G 1/2 | 0.1 bar | 10 bar | 90 °C | 12.0 | NBR | 57,55 € / Stk |
| 102938 | G 1/2 | 0.2 bar | 16 bar | 90 °C | 13.0 | NBR | 64,30 € / Stk |
| 102939 | G 1/2 | 0.2 bar | 16 bar | 140 °C | 13.0 | FPM | 67,67 € / Stk |
| 102940 | G 1/2 | 0.2 bar | 12 bar | 90 °C | 13.0 | NBR | 54,52 € / Stk |
| 102941 | G 1/2 | 0.2 bar | 12 bar | 140 °C | 13.0 | FPM | 57,55 € / Stk |
| 102942 | G 3/4 | 0.2 bar | 16 bar | 90 °C | 19.0 | NBR | 102,97 € / Stk |
| 102943 | G 1 | 0.2 bar | 16 bar | 90 °C | 25.0 | NBR | 112,64 € / Stk |
| 102944 | G 1 1/4 | 0.2 bar | 10 bar | 90 °C | 35.0 | NBR | 220,99 € / Stk |
| 102945 | G 1 1/2 | 0.2 bar | 10 bar | 90 °C | 40.0 | NBR | 233,67 € / Stk |
| 102946 | G 2 | 0.2 bar | 10 bar | 90 °C | 50.0 | NBR | 347,24 € / Stk |

More Pictures

