


Datasheet for: 106422



**3/2-way valve, man. short wing lever NC bistable G1/8 valve pos.3**

3/2-way valve, manual, Rotating lever, NC, bistable, Connection G 1/8, Operating pre. 1 - 10 bar, Operating temp. -10 °C to 60 °C . 3 valve positions only in conjunction with a second 3/2-way valve. Corresponds to a 5/3-way valve.

Type number	515.404
Article number	106422
EAN/barcode	 4047322205405
Your price	69,51 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1/8
Flow rate at 6 bar and $\Delta p$ 0.5 bar	400 NI/min
Flow rate at 6 bar and $\Delta p$ 1.0 bar	550 NI/min
Function	3/2 NC
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	1 bar
Min. temperature range	-10 °C
Operation	Bistable
Page No.	HK455
Piston	Aluminium
Sealant	NBR
Spring	Special steel
Symbol	8
Valve body	Aluminium
Valve positions	3

## Variants

<i>Article number</i>	<i>Symbol</i>	<i>Operation</i>	<i>Valve positions</i>	<i>Price</i>
106422	8	Bistable	3	69,51 € / Stk
106419	5	Monostable	2	68,22 € / Stk
106420	6	Bistable	2	68,22 € / Stk
106421	7	Monostable	3	69,51 € / Stk

## More Pictures

