


Datasheet for: 100377


Active charcoal filter »multifix-mini«, PC container, G 1/4

Active charcoal filter »multifix-mini«, PC container, 0.005 mg/m³, G 1/4, Input pressure max. 16 bar, Med./ambient temp. max. 60°C. For filtering odours out of compressed air. The activated carbon absorbs the oil vapour molecules contained in the compressed air. A separate filter route prevents activated carbon particles from entering the air flow.

Type number	FA 06 K
Article number	100377
EAN/barcode	 4047322131179
Your price	69,67 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	40.0 mm
B	122.8 mm
Bowl	Polycarbonate container
C	12.3 mm
D	110.5 mm
DN	5.0
Filter element	Activated carbon-POM
Flow rate	380 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ _p = 0.2 bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK071
Residual oil content	0.005 mg/m ³
Sealant	NBR
Series	multifix-mini
Thread	G 1/4

Variants

Article number	Thread	Flow rate	Price
100377	G 1/4	380 l/min	69,67 € / Stk
100376	G 1/8	310 l/min	65,76 € / Stk

More Pictures

