

## Datasheet for: 103371


**3-way ball valve, T-hole, Lightweight design, Rp 1**

3-way ball valve, T-hole, Lightweight design, nickel-plated brass, Medium/ambient temp. -15 °C to 100 °C, Rp 1, PN max. 25 bar . Sealing on all sides with T-bore. The lever of this model can only be turned 90° rather than 360°. Only two valve positions are therefore possible instead of four.

|                |  |
|----------------|--|
| Type number    | 1084 EL  |
| Article number | 103371   |
| EAN/barcode    | <br>4047322275842 |
| Your price     | 69,89 € / Stk  |

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                                  |                           |
|----------------------------------|---------------------------|
| A                                | 160.0 mm                  |
| B                                | 102.0 mm                  |
| Ball                             | Nickel-plated brass       |
| Bore inball                      | 23                        |
| DN                               | 25.0                      |
| Hand lever                       | Aluminium, painted black  |
| Housing                          | Nickel-plated brass       |
| L                                | 113.0 mm                  |
| Max. ambient temperature         | 100 °C                    |
| Max. medium temperature          | 100 °C                    |
| Max. operating pressure at 20 °C | 25 bar                    |
| Min. ambient temperature         | -15 °C                    |
| Min. medium temperature          | -15 °C                    |
| Page No.                         | HK293                     |
| Sealant                          | PTFE                      |
| Spring                           | Stainless steel           |
| Standard thread                  | Rp thread acc. to ISO 7-1 |
| Thread                           | Rp 1                      |
| Thread material                  | Nickel-plated brass       |

## Variants

| Article number | Thread   | DN   | Bore inball | Max. operating pressure at 20 °C | Price          |
|----------------|----------|------|-------------|----------------------------------|----------------|
| 103371         | Rp 1     | 25.0 | 23          | 25 bar                           | 69,89 € / Stk  |
| 103372         | Rp 1 1/4 | 32.0 | 29          | 16 bar                           | 101,92 € / Stk |
| 103369         | Rp 1/2   | 15.0 | 13          | 40 bar                           | 39,03 € / Stk  |
| 103374         | Rp 2     | 50.0 | 44          | 16 bar                           | 184,63 € / Stk |
| 103373         | Rp 1 1/2 | 40.0 | 35          | 16 bar                           | 137,34 € / Stk |
| 103370         | Rp 3/4   | 20.0 | 18          | 40 bar                           | 50,55 € / Stk  |

## More Pictures

