

Datasheet for: 111963


Removable Double threaded nipple, IT / ET, flat sealing, G 2

Rem. Double threaded nipple, Interior / exterior thread, flat sealing, G 2, Working pressure max. 10 bar, Stainless steel 1.4408 .

| | |
|----------------|--|
| Type number | 274.09-ES |
| Article number | 111963 |
| EAN/barcode |  4047322400985 |
| Your price | 61,70 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-----------------------|------------------|
| L1 | 89.0 mm |
| Max. working pressure | 10 bar |
| Page No. | HK799 |
| Sealant | Flat seal PTFE |
| Standard thread | DIN EN ISO 228-1 |
| Thread | G 2 |
| a/f 1 | 90.0 mm |
| a/f 2 | 68.0 mm |

Variants

| Article number | Thread | a/f 1 | a/f 2 | Price |
|----------------|---------|---------|---------|---------------|
| 111963 | G 2 | 90.0 mm | 68.0 mm | 61,70 € / Stk |
| 111958 | G 1/2 | 39.0 mm | 26.0 mm | 10,90 € / Stk |
| 111962 | G 1 1/2 | 76.0 mm | 56.0 mm | 46,43 € / Stk |
| 111955 | G 1/8 | 29.0 mm | 18.0 mm | 8,01 € / Stk |
| 111956 | G 1/4 | 29.0 mm | 18.0 mm | 8,15 € / Stk |

Variants

| Article number | Thread | a/f 1 | a/f 2 | Price |
|----------------|---------|---------|---------|---------------|
| 111961 | G 1 1/4 | 67.0 mm | 49.0 mm | 45,82 € / Stk |
| 111959 | G 3/4 | 47.0 mm | 32.0 mm | 16,08 € / Stk |
| 111957 | G 3/8 | 34.0 mm | 22.0 mm | 8,95 € / Stk |
| 111960 | G 1 | 58.0 mm | 40.0 mm | 26,20 € / Stk |

More Pictures

