


Datasheet for: 102896


2/2-solenoid valve,NO,dir. oper.,230-240V,50-60Hz,G1/8,PN0-20bar

2/2-way solenoid valve brass, NO, dir. operated, 230 - 240V, 50 - 60Hz, 16VA, Medium temp. -10°C to 140°C, FKM, G 1/8, PN 0-20bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1331
Article number	102896
EAN/barcode	 4047322158909
Your price	61,85 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	54.0 mm
B	40.0 mm
DN	2.0
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally open (NO)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	140 °C
Max. operating pressure	20 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK320
Protection IP	IP 65 (with connector socket fitted)
Sealant	FPM
Thread	G 1/8
Type	2
Valve seat	Brass

Variants

<i>Article number</i>	<i>Thread</i>	<i>Max. operating pressure</i>	<i>DN</i>	<i>Price</i>
102896	G 1/8	20 bar	2.0	61,85 € / Stk
102897	G 1/8	14 bar	2.5	61,85 € / Stk
102898	G 1/4	10 bar	3.0	61,85 € / Stk
102899	G 1/4	4 bar	4.5	61,85 € / Stk

More Pictures

