

Datasheet for: 102901



2/2-solenoid valve,NO,dir. operated, 24V DC, 8W, G1/8, PN0-14bar

2/2-way solenoid valve brass, NO, directly operated, 24V DC, 8W, Medium temp. -10°C to 140°C, FKM, G 1/8, PN - 14bar .
 Economy series available in three different versions -
 Directly operated - Combined operation - Pilot-operated For
 all applications with compressed air, neutral gases or
 low-viscosity, neutral media.

| | |
|-------------|-----------|
| Type number | MV 1342 G |
|-------------|-----------|

| | |
|----------------|--------|
| Article number | 102901 |
|----------------|--------|

| | |
|-------------|--|
| EAN/barcode | |
|-------------|--|



4047322158961

| | |
|------------|---------------|
| Your price | 61,85 € / Stk |
|------------|---------------|

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|--|
| A | 54.0 mm |
| B | 40.0 mm |
| DN | 2.5 |
| Electrical connection | For connector socket Pg 9/Pg 11 acc. to ISO 4400 |
| Function | normally open (NO) |
| Housing | Brass |
| Internal parts | Stainless steel |
| Max. ambient temperature | 80 °C |
| Max. medium temperature | 140 °C |
| Max. operating pressure | 14 bar |
| Min. ambient temperature | -10 °C |
| Min. medium temperature | -10 °C |
| Page No. | HK321 |
| Protection IP | IP 65 (with connector socket fitted) |
| Sealant | FPM |
| Thread | G 1/8 |
| Type | 2 |
| Valve seat | Brass |

Variants

| <i>Article number</i> | <i>Thread</i> | <i>Max. operating pressure</i> | <i>DN</i> | <i>Price</i> |
|-----------------------|---------------|--------------------------------|-----------|---------------|
| 102901 | G 1/8 | 14 bar | 2.5 | 61,85 € / Stk |
| 102900 | G 1/8 | 20 bar | 2.0 | 61,85 € / Stk |
| 102902 | G 1/4 | 10 bar | 3.0 | 61,85 € / Stk |
| 102903 | G 1/4 | 4 bar | 4.5 | 61,85 € / Stk |

More Pictures

